



# EC6FxxMy

P 1/1

**Cordon CAT6 F/UTP**  
**100% CUIVRE**  
**gaine PVC 250 MHz**



Remplacer xx par la longueur et y par la couleur (exemple : 1m gris EC6F1MG)

Longueur	Gris G	Jaune J	Vert V	Bleu B	Rouge R	Orange O	Violet VI	Noir N	Blanc W
0,5 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
1 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
1,5 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
2 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
3 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
5 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
7 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
10 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
15 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
20 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
25 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
30 m	✓	✓	✓	✓	✓	✓	✓	✓	✓
50 m	✓	✓	✓	✓	✓	✓	✓	✓	✓

#### Caractéristiques

- Catégorie : CAT 6
- Fréquence : 250 MHz
- Impédance : 100 Ω
- Conducteur : cuivre
- Blindage : général par feuille d'aluminium
- Norme de câblage : ANSI/TIA 568C.2 - ISO 11801
- Gaine : PVC
- Conditionnement : sachet individuel

#### Référence

DESCRIPTION

CODE

Cordon 6 F/UTP PVC

EC6FxxMy